Renegade ET 300i / ET 300iP

Portability is paramount. But so is power.





Industry


- Ship and Offshore Yards
- Civil Construction
- Pipe Construction
- Repair and Maintenance
- Heavy Fabrication
- Industrial and General Fabrication
- Mining
- Steel Erectors

The Renegade TIG are inverter based High frequency TIG (HF) and MMA/Stick machines with extreme power to weight ratio. The compact format makes it easy to carry and bring to any jobsite. Combined with high duty cycle and the ability to run the machine on long mains and welding cable makes this a superior welding machine for both onand off site applications.

The machine has an automatic input voltage sensor and can operate with any input voltage between 208V and 528V in 3-phase and 230V in single phase.

- Extreme power to weight ratio in a most compact format. Rugged composite casing for durability in the roughest environments
- Designed for extreme conditions including up to +55°C ambient temperature
- Widest input voltage tolerance and ability to run on single and three phase with cables up to 100 meters
- Easy to read and quick to set panel increasing the accuracy and reduces the down time
- Available as non pulsed and as pulsed for thin sheet metal applications
- Modular system with tool-less connection to water cooler and trolley

Visit esab.com for more information.



ET 300i

ET 300iP

| Specifications | |
|---|---|
| Primary Voltage 1 ph | 230 VAC +/- 10%, 50/60 Hz |
| Primary Voltage 3 ph | 230-480 VAC +/- 10%, 50/60 Hz |
| Fuse Slow | 16 A at 400 V |
| Energy Save Mode | 88 W at 400 V |
| Maximum Output | 300 A |
| Power Factor at Max Current | 0.96 |
| Efficiency at Max Current TIG / MMA | 88 % / 84 % |
| Open Circuit Voltage with / without VRD | 33 V / 48 V |
| TIG Welding Output 40% Duty Cycle 60% Duty Cycle 100% Duty Cycle | 300 A / 22.0 V 250 A / 20.0 V 200 A / 18.0 V |
| MMA Welding Output 40% Duty Cycle 60% Duty Cycle 100% Duty Cycle | 300 A / 32.0 V 250 A / 30.0 V 200 A / 28.0 V |
| Current Range | 5 – 300 A (TIG and MMA) |
| Approvals | CE |
| Protection Class | IP23 |
| Mains Cable | 3 m, 4×2,5 mm ² (4×4 mm ² with 230 V) |
| Supply Plug | CEE 16 A |
| Dimensions, Lx W x H | 460 x 200 x 320 mm |
| Weight without / with Cooler | 16.9 kg / 26.9 kg |

Ordering Information Renegade ET 300i incl 3 m mains cable and plug 0445100900

Renegade ET 300iP incl 3 m mains cable and plug

| Ordering Information | |
|--|------------|
| Shoulder strap | 0445197880 |
| Trolley 2-wheel for Renegade | 0460330881 |
| TXH 201 TIG Torch 4 m | 0700300552 |
| TXH 201 TIG Torch 8 m | 0700300555 |
| TXH 252w TIG Torch 4 m | 0700300855 |
| TXH 252w TIG Torch 8 m | 0700300856 |
| EC 1000 Water Cooler | 0445045880 |
| ER 1 Remote Control incl. 5 m cable and 6-pin connector | 0445536881 |
| ER 1 Remote Control incl. 10 m cable and 6-pin connector | 0445536882 |
| ER 1 Remote Control incl. 25 m cable and 6-pin connector | 0445536883 |
| ER 1F Foot Control incl. 5 m cable and 6-pin connector | 0445550881 |
| ER 1F Foot Control incl. 10 m cable and 6-pin connector | 0445550882 |

0445100920

When choosing a top-performing welding machine you need top-performing ESAB Filler Metals. Learn more at esab.com/fillermetals today.





